

## **Camera Bellows**

Customer Information	<b>Project Information</b>			
Company	Project/Reference		(	Qty Required
Address	Application			
City State Zip				
Contact	Replacement Cover	☐ New	Design	Nabell Design
PhoneFax	Acceleration	_ Speed _		Cycles/day
Email	Requested Material:			Nabell Recomended
Application Information	If unit of mea	sure is not s	hown, pleas	e specify
Bellows/Cover Construction:   Nabell Recommendation	☐ Heat-Sealed ☐ F	olded	☐ Molded	☐ RF Sealed
Orientation: Please supply a sketch/drawing/CAD File/model (.dwg, .dxf,	.stp, .sldprt) or photos			
☐ Horizontal ☐ Vertical				
Environmental Conditions/Protection (information ma	ay be applicable for industria	I camera appli	cations)	
☐ Chemicals/Coolant specify type, % concentration, MSDS_			Misc Info	ormation
	leavy Spray	Submerged	☐ Food	Grade/FDA
Chips/Particles specify type, size & temp at bellows		⊓°F ⊓°C		
Pressures internal external difference			☐ Wate	r Jet
Clean Room class   ISO FED Electrostatic (spe	ecify)		☐ Plasn	na Cutter
Water/Moisture specify type			☐ Outdo	oors
Safety/Dust Cover specify			☐ Medio	cal
Weld Spatter/Sparks (Distance from bellows)			☐ Other	specify
	np Range to			
Standards/Requirements				
□ REACH: □ RoHS:	COC:		☐ FAIR:	
CONFLICT Minerals:				
Mounting Options				
End 1: ☐ Flange ☐ Holes required (specify/provide drawing) ☐ Hook and Loop (velcro) ☐ Cuff Attachment Dimer			•	No Flange required
End 2: ☐ Flange ☐ Holes required (specify/provide drawing) ☐ Hook and Loop (velcro) ☐ Cuff Attachment Dimer			•	No Flange required
Will bellows be supported during operation?   Lens Board  (Nabell recommends providing a method of capture to control any of		Rod □ Other		


Phone: 704-986-2455 Fax: 704-986-2456 Email: sales@nabell.com Website: www.nabell.com




## **Camera Bellows**

## **Please Select style**


☐ Square/Rectangle




☐ Tapered




☐ Polygonal




□ Round



□ Oval




□ Cornerless



Dimensions: Please provide drawing or model (.dwg, .dxf, .stp, .sldprt)

Α	F	Please specify unit of measure
В	G	☐ MM ☐ INCH
С	н	
D	MIN	(Compressed)
E	MAX	(Extended)

(Nabell recommends providing a method of capture to control any deviation from the intended travel path)



Phone: 704-986-2455 Fax: 704-986-2456 Email: sales@nabell.com Website: www.nabell.com