

Laser Bellows

Customer Information	Project Information			
Company	Project/Reference		Qty Required	
Address	Application			
City State Zip				
Contact	Replacement Cover	New Design	Nabell Design	
Phone Fax	Acceleration	Speed	Cycles/day	
Email	Requested Material:		☐ Nabell Recomende	
Application Information	If unit of measure is not shown, please specify			
Bellows/Cover Construction: Nabell Recommendation	☐ RF/Heat-Sealed ☐ Folde	d ☐ Sewn	☐ Molded	
Orientation: Please supply a sketch/drawing/CAD File/model (.dwg, .dxf,	.stp, .sldprt) or photos			
☐ Horizontal ☐ Vertica	Va. Ž	□ Crossrai	Va Ž	
Environmental Conditions/Protection				
☐ Chemicals/Coolant specify type, % concentration, MSDS		Misc	_ Misc Information	
	Heavy Spray ☐ Flooded ☐ Sub		ood Grade/FDA	
Chips/Particles specify type, size & temp at bellows		- □°C □ L	aser	
Pressures internal external difference		□ W	/ater Jet	
Clean Room class	ecify)	D	lasma Cutter	
Water/Moisture specify type		O	utdoors	
Safety/Dust Cover specify			edical	
Weld Spatter/Sparks (Distance from bellows)		o	ther specify	
Ambient Temp Range to Intermittant Ten	np Range to □°F	□°C _		
Standards/Requirements				
□ REACH: □ RoHS:				
CONFLICT Minerals:	Special Req:			
Mounting Options				
End 1: Flange Holes required (specify/provide drawing) Hook and Loop (velcro) Cuff Attachment Dimer				
End 2: ☐ Flange ☐ Holes required (specify/provide drawing) ☐ Hook and Loop (velcro) ☐ Cuff Attachment Dimer		•	☐ No Flange required	
Will bellows be supported during operation? C-Channel (Nabell recommends providing a method of capture to control any of the control and the				


Phone: 704-986-2455 Fax: 704-986-2456 Email: sales@nabell.com Website: www.nabell.com




Laser Bellows

Please Select style


☐ Square/Rectangle




□ Tapered




☐ Polygonal




□ Round



□ Oval



□3 Sided/Way Cover



Dimensions: Please provide drawing or model (.dwg, .dxf, .stp, .sldprt)

 A
 F
 Please specify unit of measure


 B
 G
 MM
 INCH

 C
 H
 INCH

 D
 MIN
 (Compressed)

 E
 MAX
 (Extended)

(Nabell recommends providing a method of capture to control any deviation from the intended travel path)



Phone: 704-986-2455 Fax: 704-986-2456 Email: sales@nabell.com Website: www.nabell.com